



MSDS

Material Safety Data Sheet

PET

Page 1/4

Revision Date: 2015.03.05 (Rev.0)

Product Name: PET
Chemical Name: POLYETHYLENETEREPTHALATE
CAS NO: 25038-59-9 (POLYMER)
Product Use: Engineering Plastic Stock Shape for Machining
Company Identification: PSR Industrial Ltd.
Namdongseo-ro, Namdong-Gu, Incheon-City, Korea
(TEL:82-32-677-2971, FAX:82-32-677-2974)

Hazard Identification

Eye

Dust and particles, like other inert materials, are mechanically irritating to eyes.

Skin

Hot and molten material has the potential to cause thermal burns.

Inhalation

Shapes not respirable.

Ingestion

No specific information available on the product.

Composition, information on Ingredients

Additives not hazardous by 29 CFR 1910.1200.

Identity	CAS#	Concentration(%)
NA	NA	NA

First Aid Measures

Eye

Immediately flush eyes with plenty of water. Seek medical attention if discomfort persists.

Skin

If hot and molten PET contact skin, cool rapidly with cold water. If PET is stuck to skin, do not remove, and seek medical attention. And allow adhered PET to come off naturally.

Inhalation

PET is not likely to be inhaled due to physical form. When gas from molten PET is inhaled, move to fresh air.

Ingestion

If a significant quantity has been swallowed, give plenty of water to dilute. Seek medical attention.

Note to Physicians

Processing vapors may cause irritation to the eyes, skin and respiratory tract. In cases of severe exposure, nausea and headache can also occur.



MSDS

Material Safety Data Sheet
PET

Page 2/4
Revision Date: 2015.03.05 (Rev.0)

Fire Fighting Measures

Flash Point : >355°C (>671°F)

Autoignition Temperature : >420°C (>788°F)

Unusual Fire, Explosion Hazards : None Known.

Hazardous Product of Combustion

Fire will produce hazardous decomposition products such as carbonmonoxide, carbon dioxide, dense black smoke, aldehydes and organic acids.

Extinguishing Media : Dry chemical, CO2 or alcohol-resistant foam.

Firefighting Instructions

Firefighters should wear self-contained breathing apparatus and full fire-fighting turn-out gear (bunker gear). Product burns with a very hot, but very faint blue flame. Water, foam and dry chemical may cause damage to electrical equipment.

Accidental Release Measures

Personal precaution

Sweeping to prevent fall.

Environmental protection

No special measures.

Handling and Storage

Handling

During machining of the stock shapes, evacuate swarf to prevent slipping hazard.

Storage

Store in well-ventilated area away from heat and sunlight.

Exposure Controls / Personal Protection

Engineering Controls

A continuous supply of fresh air to the workplace together with removal of processing fumes through exhaust systems is recommended.

Protective Equipment

Eyes: Wear safety glasses with side shields should be sufficient for most processing and machining runs.

Skin: When thermal or melt processing, wear long pants, long sleeves and well insulated gloves.



MSDS

Material Safety Data Sheet
PET

Page 3/4
Revision Date: 2015.03.05 (Rev.0)

Exposure Guidelines

Operations involving grinding and machining of parts should be reviewed to assure that particulate levels are kept below recommended standard.

Ingredient	Agency	Value
Nuisance/Inert Dust	PEL(OSHA)	15mg/cm ³

Physical and Chemical Properties

Appearance:	Solid
Smell:	None
PH:	Not applicable
Water Solubility:	Insoluble
Boiling Point:	Not applicable
Melting Point:	255°C (491°F)
Vapor Pressure:	Not applicable
Specific Gravity:	1.33 ~ 1.43g/cm ³

Stability and Reactivity

Chemical Stability

Stable under normal conditions of use and storage.

Materials to Avoid

Strong oxidants and bases.

Hazardous Decomposition Products

No specific data.

Toxicological Information

Acute Toxicity: No information available.

Irritation/Corrosion: No information available.

Sensitiser: No information available.

Mutagenicity: No information available.

Chronic Toxicity: There are no known carcinogenic chemicals in this product.

Carcinogenicity: No information available.

Reproductive Toxicity: No information available.

Teratogenicity: No information available.



MSDS

Material Safety Data Sheet
PET

Page 4/4
Revision Date: 2015.03.05 (Rev.0)

Ecological Information

Ecotoxicity: No specific information available on the product.

Environmental Information: This material is considered to be non-biodegradable.

Aquatic Toxicity: Toxicity is expected to be low based on insolubility of polymer in water.

Disposal Considerations

Recycling is encouraged. Dispose in accordance with local regulations.

Transportation Information

UN number: Not regulated as a hazardous material.

Class: Not applicable.

Proper shipping name: Not applicable.

Packing group: Not applicable.

Marine pollutant: Not applicable.

Regulatory Information

TSCA: All ingredients are listed.

SARA 313: This product is not contain any toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372.

California Proposition 65: This product does not contain components known to the State of California to cause cancer and/or reproductive effects.

Other Information

This product is not intended for use in medical applications involving permanent implantation in the human body. The information contained herein is based on the present state of our knowledge. We don't suggest or guarantee that any hazards listed herein are the only ones that exist. PSR Industrial Ltd. Makes no warranty of any kind concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and this material may aggravate the effects of other materials.

Users have the sole responsibility to determine the suitability of the materials of any use and the manner of use contemplated. Users must meet all applicable safety and health standards.